



UNIVERSAL COOPERATE LTD.

Model UCL-WHP200
Coaxial Fixed Attenuator
200 Watts DC-10GHz



Model Number	Frequency Range (GHz)	Attenuation Value & Accuracy (dB)				Max VSWR
		10	20	30	40	
UCL-WHP200-2.5	DC-2.5	±0.5	±0.5	±0.5	±0.5	1.15
UCL-WHP200-4	DC-4	±0.5	±0.5	±0.5	±0.5	1.25
UCL-WHP200-6	DC-6	/	±0.6	±0.5	±0.5	1.30
UCL-WHP200-8	DC-8	/	±0.75	±0.75	±0.75	1.35
UCL-WHP200-10	DC-10	/	±1.0	±1.0	±1.0	1.45

Note: XX refer to attenuation value in dB

Coaxial fixed attenuators are used in absorbing energy of transmission line, expanding power range and controlling power level, they are also used in accurately measuring power or spectrum of RF microwave transmitters accompany with small power meter, comprehensive tester or spectrum analyzer.

UCL-WHP200 serial coaxial fixed attenuators' average power from 50W-500W, frequency range from DC-10GHz and feature wide frequency band, low VSWR, flatness attenuation value, excellent capacity in anti-pulse and anti-burnout.

NOMINAL IMPEDANCE: 50Ω

AVERAGE POWER: 200W average to 25°C ambient temperature, derated linearly to 20W @ 125°C.

PEAK POWER: 5KW (5μs pulse width with 4% duty cycle)

3rd ORDER INTERMODULATION(Optional):

Reflected Levels(IM3) <-100dBc with two input signals @935MHz and 960MHz with average carrier power levels of +43dBm each.


TEMPERATURE RANGE: -55°C~+125°C

CONNECTOR TYPE: 7/16(DC-4),N

WEIGHT: 2.2Kg

PHYSICAL DIMENSIONS: 234×130×75mm

Outline Drawings



* Dimensions are given in mm and tolerance ±2%.

** VSWR varies according to frequency and attenuation value.

*** VSWR and dimensions refer to connector type N.